

# VRLS E-4

## V-STEEL R-LUG S



The V-STEEL R-LUG S radial tire is designed in a variety of sizes for quarry, coal and mining services and feature a deep rock non-directional tread pattern. Certain sizes are low profile/low inflation pressure for cut resistance and extended tread life.

### SPECIALIZED FEATURES

- Deep non-directional rock service tread pattern
- Excellent haulage performance on rock, gravel, or packed earth
- Special compounds provide excellent wear and cut resistance



CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT.	OTD (32ND)	OVERALL DIAMETER	OVERALL WIDTH
SMALL TUBELESS	14.00R25	3*	E2A	E-4	263419	430	49	55.2	15.3
	16.00R25	2*	E1A	E-4	261440	600	57	60.3	17.6
LARGE TUBELESS	24.00R35	2*	E1A	E-4	275883	1,730	74	85.6	26.0
	24.00R35	2*	E2A	E-4	419141	1,730	74	85.6	26.0
	24.00R35	2*	E2A LS	E-4	422169	1,730	74	85.6	26.0
	24.00R49	2*	E2A	E-4	276332	2,330	74	99.6	25.8
	27.00R49	2*	E1A	E-4	275905	3,010	84	105.8	29.5
	27.00R49	2*	E2A	E-4	276340	3,010	84	105.8	29.5
	27.00R49	2*	E2A LS	E-4	419648	3,010	84	105.8	29.5
	27.00R49	2*	E3A UH	E-4	420042	3,010	84	105.8	29.5
	33.00R51	2*	E1A	E-4	422045	4,840	99	119.5	36.7
	33.00R51	2*	E2A	E-4	419168	4,840	99	119.5	36.7
GIANT TUBELESS	33.00R51	2*	E2A LS	E-4	419540	4,840	99	119.5	36.7
	33.00R51	2*	E3A	E-4	419192	4,840	99	119.5	36.7
	36.00R51	2*	E1A	E-4	421898	5,530	109	126.1	40.0
	36.00R51	2*	E2A	E-4	276367	5,530	109	126.1	40.0
	36.00R51	2*	E2A LS	E-4	419559	5,530	109	126.1	40.0
	36.00R51	2*	E3A	E-4	276405	5,530	109	126.1	40.0
	37.00R57	2*	E1A	E-4	421707	6,520	110	134.3	41.1
	37.00R57	2*	E2A	E-4	276375	6,520	110	134.3	41.1
37.00R57	2*	E2A LS	E-4	419567	6,520	110	134.3	41.1	
37.00R57	2*	E3A	E-4	419583	6,520	110	134.3	41.1	

UH: Ultra Heat  
 LS: Special Cut Resistant

